




SPC - 3



1



3




4


Werkstoff Grauguss EN-GJL-200

code	Rillen	dp	de	Typ	Spann- buchsen	Bohrung max	Dm	Di	E	F	L	R	S	kg
SPC 200 03	3	200	209,6	3	2517	65		144		85	45	20	20	10,20
SPC 212 03	3	212	221,6	3	3020	75		156		85	51	17	17	11,00
SPC 224 03	3	224	233,6	3	3020	75		168		85	51	17	17	12,00
SPC 236 03	3	236	245,6	3	3020	75		180		85	51	17	17	13,00
SPC 250 03	3	250	259,6	3	3020	75		194		85	51	17	17	15,50
SPC 265 03	3	265	274,6	1	3535	90	175			85	89	4		17,20
SPC 280 03	3	280	289,6	1	3535	90	175			85	89	4		19,40
SPC 300 03	3	300	309,6	4	3535	90	175	244		85	89	2	2	22,60
SPC 315 03	3	315	324,6	4	3535	90	175	259		85	89	2	2	22,50
SPC 335 03	3	335	344,6	4	3535	90	175	279		85	89	2	2	23,50
SPC 355 03	3	355	364,6	4	3535	90	175	299		85	89	2	2	24,80
SPC 375 03	3	375	384,6	4	3535	90	175	319		85	89	2	2	25,50
SPC 400 03	3	400	409,6	4	3535	90	175	344		85	89	2	2	26,40
SPC 425 03	3	425	434,6	4	3535	90	175	369		85	89	2	2	27,00
SPC 450 03	3	450	459,6	4	3535	90	175	394		85	89	2	2	28,60
SPC 475 03	3	475	484,6	4	3535	90	175	419		85	89	2	2	30,00
SPC 500 03	3	500	509,6	4	3535	90	175	444		85	89	2	2	31,90
SPC 530 03	3	530	539,6	4	3535	90	175	474		85	89	2	2	34,50
SPC 560 03	3	560	569,6	4	3535	90	175	504		85	89	2	2	37,00
SPC 630 03	3	630	639,6	4	4040	100	210	574		85	102	8,5	8,5	44,50
SPC 800 03	3	800	809,6	4	4545	110	242	737		85	114	14,5	14,5	65,00
SPC1000 03	3	1000	1009,6	4	5050	125	267	937		85	127	21	21	93,00
SPC1250 03	3	1250	1259,6	4	5050	125	267	1187		85	127	21	21	101,00


SPC - 4




3



4



5




6


Werkstoff Grauguss EN-GJL-200

code	Rillen	dp	de	Typ	Spann- buchsen	Bohrung max	Dm	Di	E	F	L	R	S	kg
SPC 200 04	4	200	209,6	3	3020	75		144		111	51	30	30	12,50
SPC 212 04	4	212	221,6	3	3020	75		156		111	51	30	30	13,50
SPC 224 04	4	224	233,6	3	3535	90		168		111	89	11	11	15,00
SPC 236 04	4	236	245,6	3	3535	90		180		111	89	11	11	18,20
SPC 250 04	4	250	259,6	3	3535	90		194		111	89	11	11	21,70
SPC 265 04	4	265	274,6	3	3535	90		209		111	89	11	11	23,00
SPC 280 04	4	280	289,6	6	3535	90	175	224	18	111	89	11	11	24,10
SPC 300 04	4	300	309,6	6	3535	90	175	244	20	111	89	11	11	25,00
SPC 315 04	4	315	324,6	5	3535	90	175	259		111	89	11	11	26,40
SPC 335 04	4	335	344,6	5	3535	90	175	279		111	89	11	11	27,50
SPC 355 04	4	355	364,6	5	3535	90	175	299		111	89	11	11	29,30
SPC 375 04	4	375	384,6	5	3535	90	175	319		111	89	11	11	31,00
SPC 400 04	4	400	409,6	5	3535	90	175	344		111	89	11	11	32,80
SPC 425 04	4	425	434,6	5	3535	90	175	369		111	89	11	11	33,40
SPC 450 04	4	450	459,6	5	3535	90	175	394		111	89	11	11	36,80
SPC 475 04	4	475	484,6	5	3535	90	175	419		111	89	11	11	38,00
SPC 500 04	4	500	509,6	5	3535	90	175	444		111	89	11	11	40,00
SPC 530 04	4	530	539,6	5	4040	100	210	474		111	102	4,5	4,5	45,00
SPC 560 04	4	560	569,6	5	4040	100	210	504		111	102	4,5	4,5	50,00
SPC 630 04	4	630	639,6	4	4545	110	242	574		111	114	1,5	1,5	58,00
SPC 710 04	4	710	719,6	4	5050	125	267	654		111	127	8	8	64,00
SPC 800 04	4	800	809,6	4	5050	125	267	737		111	127	8	8	76,50
SPC1000 04	4	1000	1009,6	4	5050	125	267	937		111	127	8	8	105,00
SPC1250 04	4	1250	1259,6	4	5050	125	267	1187		111	127	8	8	178,00


SPC - 5




3



4



5




6


Werkstoff Grauguss EN-GJL-200

code	Rillen	dp	de	Typ	Spann- buchsen	Bohrung max	Dm	Di	E	F	L	R	S	kg.
SPC 200 05	5	200	209,6	3	3535	90		144		136	89	23,5	23,5	14,70
SPC 212 05	5	212	221,6	3	3535	90		156		136	89	23,5	23,5	15,00
SPC 224 05	5	224	233,6	3	3535	90		168		136	89	23,5	23,5	17,20
SPC 236 05	5	236	245,6	3	3535	90		180		136	89	23,5	23,5	20,20
SPC 250 05	5	250	259,6	3	3535	90		194		136	89	23,5	23,5	23,50
SPC 265 05	5	265	274,6	3	3535	90		209		136	89	23,5	23,5	25,50
SPC 280 05	5	280	289,6	3	3535	90		224		136	89	23,5	23,5	27,20
SPC 300 05	5	300	309,6	6	3535	90	175	244	20	136	89	23,5	23,5	28,50
SPC 315 05	5	315	324,6	5	3535	90	175	259		136	89	23,5	23,5	29,50
SPC 335 05	5	335	344,6	5	3535	90	175	279		136	89	23,5	23,5	31,00
SPC 355 05	5	355	364,6	5	3535	90	175	299		136	89	23,5	23,5	33,50
SPC 375 05	5	375	384,6	5	3535	90	175	319		136	89	23,5	23,5	36,00
SPC 400 05	5	400	409,6	5	3535	90	175	344		136	89	23,5	23,5	37,00
SPC 425 05	5	425	434,6	5	3535	90	175	369		136	89	23,5	23,5	43,00
SPC 450 05	5	450	459,6	5	4040	100	210	394		136	102	17	17	46,00
SPC 475 05	5	475	484,6	5	4040	100	210	419		136	102	17	17	50,30
SPC 500 05	5	500	509,6	5	4040	100	210	444		136	102	17	17	54,00
SPC 530 05	5	530	539,6	5	4545	110	240	474		136	114	11	11	57,50
SPC 560 05	5	560	569,6	5	4545	110	242	504		136	114	11	11	61,00
SPC 630 05	5	630	639,6	5	5050	125	267	574		136	127	4,5	4,5	75,00
SPC 710 05	5	710	719,6	5	5050	125	267	654		136	127	4,5	4,5	79,00
SPC 800 05	5	800	809,6	5	5050	125	267	737		136	127	4,5	4,5	96,50
SPC1000 05	5	1000	1009,6	5	5050	125	267	937		136	127	4,5	4,5	139,00
SPC1250 05	5	1250	1259,6	5	5050	125	267	1187		136	127	4,5	4,5	196,00


SPC - 6



3



5




6


Werkstoff Grauguss EN-GJL-200

code	Rillen	dp	de	Typ	Spann- buchsen	Bohrung max	Dm	Di	E	F	L	R	S	kg
SPC 200 06	6	200	209,6	3	3535	90		144		162	89	36,5	36,5	17,50
SPC 212 06	6	212	221,6	3	3535	90		156		162	89	36,5	36,5	19,00
SPC 224 06	6	224	233,6	3	3535	90		168		162	89	36,5	36,5	21,00
SPC 236 06	6	236	245,6	3	3535	90		180		162	89	36,5	36,5	23,00
SPC 250 06	6	250	259,6	3	3535	90		194		162	89	36,5	36,5	26,00
SPC 265 06	6	265	274,6	3	3535	90		209		162	89	36,5	36,5	27,00
SPC 280 06	6	280	289,6	6	3535	90	175	224	20	162	89	36,5	36,5	29,00
SPC 300 06	6	300	309,6	6	3535	90	175	244	20	162	89	36,5	36,5	31,50
SPC 315 06	6	315	324,6	5	3535	90	175	259		162	89	36,5	36,5	33,20
SPC 335 06	6	335	344,6	5	3535	90	175	279		162	89	36,5	36,5	35,00
SPC 355 06	6	355	364,6	5	3535	90	175	299		162	89	36,5	36,5	37,00
SPC 375 06	6	375	384,6	5	4040	100	210	319		162	102	30	30	42,50
SPC 400 06	6	400	409,6	5	4040	100	210	344		162	102	30	30	47,50
SPC 425 06	6	425	434,6	5	4040	100	210	369		162	102	30	30	55,60
SPC 450 06	6	450	459,6	5	4545	110	242	394		162	114	24	24	62,50
SPC 475 06	6	475	484,6	5	4545	110	242	419		162	114	24	24	65,00
SPC 500 06	6	500	509,6	5	4545	110	242	444		162	114	24	24	68,20
SPC 530 06	6	530	539,6	5	5050	125	265	474		162	127	17,5	17,5	73,00
SPC 560 06	6	560	569,6	5	5050	125	267	504		162	127	17,5	17,5	86,00
SPC 630 06	6	630	639,6	5	5050	125	267	574		162	127	17,5	17,5	96,00
SPC 710 06	6	710	719,6	5	5050	125	267	654		162	127	17,5	17,5	102,00
SPC 800 06	6	800	809,6	5	5050	125	267	737		162	127	17,5	17,5	120,00
SPC1000 06	6	1000	1009,6	5	5050	125	267	937		162	127	17,5	17,5	160,00
SPC1250 06	6	1250	1259,6	5	5050	125	267	1187		162	127	17,5	17,5	232,70


SPC - 8



3



5




6


Werkstoff Grauguss EN-GJL-200

code	Rillen	dp	de	Typ	Spann- buchsen	Bohrung max	Dm	Di	E	F	L	R	S	kg
SPC 200 08	8	200	209,6	3	3535	90		144		213	89	62	62	17,90
SPC 212 08	8	212	221,6	3	3535	90		156		213	89	62	62	24,00
SPC 224 08	8	224	233,6	3	3535	90		168		213	89	62	62	25,00
SPC 236 08	8	236	245,6	3	3535	90		180		213	89	62	62	27,00
SPC 250 08	8	250	259,6	3	3535	90		194		213	89	62	62	30,50
SPC 265 08	8	265	274,6	3	3535	90		209		213	89	62	62	34,50
SPC 280 08	8	280	289,6	3	3535	90		224		213	89	62	62	38,50
SPC 300 08	8	300	309,6	3	4040	100		244		213	102	55,5	55,5	47,50
SPC 315 08	8	315	324,6	3	4040	100		259		213	102	55,5	55,5	51,00
SPC 335 08	8	335	344,6	6	4040	100	210	279	50	213	102	55,5	55,5	44,50
SPC 355 08	8	355	364,6	5	4040	100	210	299		213	102	55,5	55,5	57,00
SPC 375 08	8	375	384,6	5	4545	110	242	319		213	114	49,5	49,5	62,00
SPC 400 08	8	400	409,6	5	4545	110	242	344		213	114	49,5	49,5	66,50
SPC 425 08	8	425	434,6	5	4545	110	242	369		213	114	49,5	49,5	75,00
SPC 450 08	8	450	459,6	5	5050	125	267	394		213	127	43	43	80,50
SPC 475 08	8	475	484,6	5	5050	125	267	419		213	127	43	43	85,50
SPC 500 08	8	500	509,6	5	5050	125	267	444		213	127	43	43	90,20
SPC 530 08	8	530	539,6	5	5050	125	267	474		213	127	43	43	92,50
SPC 560 08	8	560	569,6	5	5050	125	267	504		213	127	43	43	109,00
SPC 630 08	8	630	639,6	5	5050	125	267	574		213	127	43	43	120,20
SPC 710 08	8	710	719,6	5	5050	125	267	654		213	127	43	43	124,70
SPC 800 08	8	800	809,6	5	5050	125	267	737		213	127	43	43	148,00
SPC1000 08	8	1000	1009,6	5	5050	125	267	937		213	127	43	43	188,20
SPC1250 08	8	1250	1259,6	5	5050	125	267	1187		213	127	43	43	260,00


SPC - 10



3



5



6

Werkstoff Grauguss EN-GJL-200

code	Rillen	dp	de	Typ	Spann- buchsen	Bohrung max	Dm	Di	E	F	L	R	S	kg
SPC 250 10	10	250	259,6	3	4040	100		194		264	102	81	81	39,60
SPC 280 10	10	280	289,6	3	4040	100		224		264	102	81	81	51,40
SPC 300 10	10	300	309,6	3	4545	110		244		264	114	75	75	57,90
SPC 315 10	10	315	324,6	3	4545	110		259		264	114	75	75	72,00
SPC 335 10	10	335	344,6	3	4545	110		279		264	114	75	75	76,50
SPC 355 10	10	355	364,6	3	4545	110		299		264	114	75	75	83,40
SPC 400 10	10	400	409,6	6	5050	125	267	344	70	264	127	68,5	68,5	80,50
SPC 450 10	10	450	459,6	5	5050	125	267	394		264	127	68,5	68,5	100,90
SPC 500 10	10	500	509,6	5	5050	125	267	444		264	127	68,5	68,5	114,00
SPC 560 10	10	560	569,6	5	5050	125	267	504		264	127	68,5	68,5	125,00
SPC 630 10	10	630	639,6	5	5050	125	267	574		264	127	68,5	68,5	145,00
SPC 710 10	10	710	719,6	5	5050	125	267	654		264	127	68,5	68,5	165,00
SPC 800 10	10	800	809,6	5	5050	125	267	737		264	127	68,5	68,5	182,00
SPC1000 10	10	1000	1009,6	5	5050	125	267	937		264	127	68,5	68,5	240,00
SPC1250 10	10	1250	1259,6	5	5050	125	267	1187		264	127	68,5	68,5	280,00